



WESTERN COLLOID

Material Safety Data Sheet

#925 Clear Acrylic Skylight Coating

(Clear, Water Based Roof Coating)

Date: 07/15/2009

Chemical Formula: Mixture

SECTION 1 - MANUFACTURER INFORMATION

Manufacturer's Name:	Western Colloid S.C., Inc.	Western Colloid N.C., Inc.
Address:	654 E. 60 th St., Los Angeles, CA 90001	700 71 st Ave., Oakland, CA 94621
Emergency Phone No.:	323-231-8292	510-430-0270
Information Phone No.:	323-231-8292	510-430-0270

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

<u>Ingredient Name</u>	<u>CAS Number</u>	<u>%</u>	<u>TLV</u>
Texanol	25265-77-4	<5	n/a
Balance non-hazardous (water and acrylic polymers) *		>95	
water	7732-18-5		n/a
acrylic polymer	25852373		n/a

SECTION III - PHYSICAL DATA

Appearance: Translucent, Milky liquid.	Odor: Mild Odor
V.O.C Actual = <39 gm/ltr	Regulatory = <96 gm/ltr
Boiling Point: 212°F	Evaporation Rate (Butyl Acetate=1): <1
Vapor Pressure (mmHG): 17.5	Specific Gravity (Water=1): 1.03
Water Solubility: Dilutable	Melting Point: N/A
Vapor Density (Air=1): <1	% Volatile by Weight: 42 (water)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Auto Ignition Temperature: N/A
Flash Point: N/A
Extinguishing Media: None needed. (water base)
Unusual Fire or Explosion Hazards: Dried product can burn. Use water, foam, CO₂ or dry chemical extinguishers.
Special Fire-Fighting Procedures: Use breathing apparatus in enclosed areas.

SECTION V - PHYSICAL HAZARDS (REACTIVITY DATA)

Stability (Thermal, Light): Stable
Incompatibility (Material to Avoid): Minerals that react with water.
Hazardous Polymerization: Will not occur
Hazardous Decomposition Products: Burning may produce carbon monoxide and carbon dioxide.

SECTION VI - HEALTH HAZARDS

Acute: Acute: No evidence of adverse effects from available information.

Chronic: Prolonged contact may cause transient reddening of skin and eye irritation.

Medical conditions aggravated by exposure: None Known

#925 Clear Acrylic Skylight Coating - Page 2

SECTION VII - EMERGENCY & FIRST AID

Inhalation: Residual monomer vapors may be irritating to eyes, mucous membranes and respiratory tract. May produce symptoms of headache and nausea in poorly ventilated areas. Remove to fresh air.

Skin: If redness or rash occurs...wash with soap and warm water.

Eyes: Rinse with clean water

Ingestion: Should not occur. If swallowed do not induce vomiting, consult physician.

SECTION VIII - INDUSTRIAL HYGIENE CONTROL MEASURES

Ventilation: If spraying in enclosed or confined area, maintain proper ventilation to keep air contaminant below permissible exposure limit.

Respiratory Protection: If mist is present or if sprayed in enclosed areas, use MSHA/NIOSH approved mask for mist.

Protective Gloves: Impervious to water.

Eye Protection: Safety glasses or goggles. Available eye wash.

Other Protective Equipment: Protective clothing to avoid skin contact.

SECTION IX - ENVIRONMENTAL PROTECTION INFORMATION

Steps in Case of Spill: Enclose with diking material. Scoop up wet material for reclamation and reuse. Let residue dry or wash down.

Waste Disposal Method: Standard waste disposal for dry material subject to local and Federal regulations. Conservation and Recovery Act (RCRA) (40CFR 261).

Handling and Storage Precautions: Store containers in cool dry area away from direct sunlight. Protect from freezing. Keep lids tightly closed when not in use.

DOT Shipping Requirements: Not DOT regulated.

SECTION X - OTHER INFORMATION

	Health	Flammability	Reactivity
HMIS* Rating:	1	0	0
NFPA** Rating			

Notice: These ratings involve data and interpretations that may vary from company to company and are intended only for rapid, general identification of the magnitude of the specific hazard. TO DEAL ADEQUATELY WITH THE SAFE HANDLING OF THIS MATERIAL ALL OF THE INFORMATION CONTAINED IN THIS MSDS MUST BE CONSIDERED. The customer is responsible for determining the proper personal protective equipment needed for its particular use of this material.

* Hazardous Materials Identification Systems [HMIS] Revised RAW MATERIALS RATING MANUAL, National Paint & Coatings Association, Fall 1984.

** NFPA 704 Standard System for the Identification of the Fire Hazards of Materials, National Fire Protection Association, 1985

The information contained herein is furnished without warranty of any kind. Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers. Information on this form is furnished solely for the purpose of compliance with OSHA Hazard Communication Standard, 20 CFR 1910.1200, the Workplace Hazardous Material Information System (WHMIS), and shall not be used for any other purpose.