



## TECHNICAL BULLETIN

### “FLEX CRETE” Acrylic Crack Sealant WCP #652

FLUID APPLIED REINFORCED ROOFING • REFLECTIVE COATING SYSTEMS

#### 1.0 DESCRIPTION AND RECOMMENDED USE

FLEX-CRETE (WCP #652) is a light gray highly modified acrylic emulsion with a selected plasticizer to achieve greater flexibility. Designed for filling narrow concrete cracks up to 1/2" in width and depth. It is ready to use on all concrete surfaces such as roadways, airports, driveways, patios, walkways, garage floors, athletic courts, traffic safety islands and playgrounds.

#### 2.0 SURFACE PREPARATION

Surface must be dry, clean, and free from all loose material, dirt and dust.

#### 3.0 APPLICATION

Lightly stir or shake before using. Use as is. Fill cracks completely. Before it sets up, scrape excess from surfaces using a rubber squeegee with a V-shape notch to leave a bead. Sprinkle silica sand (lightly) before it sets up, to promote adhesion or bond of any sealer or stain. FLEX-CRETE will set under good conditions in 8 to 24 hours, depending on weather and size of crack. Additional time or second application may be required for deeper cracks. Do not use when rain is forecast, when cracks are wet or when temperature is below 50 degrees Fahrenheit.

#### 4.0 COVERAGE

Indefinite. For estimation purposes - up to 150 linear feet of 1/2" x 1/4" depth crack per gallon.

#### 5.0 CLEAN UP

Use clean water before product has dried. Wash tools in water. Dried product may be removed using WCP #2000 or paint thinner.

#### 6.0 PRECAUTIONS

Do not store in direct sunlight or where temperatures exceed 100 degrees Fahrenheit. Container should be closed when not in use. Keep out of reach of children. Do not use when rain is forecast, on wet surfaces or when asphalt and air temperature is below 55 degrees Fahrenheit. Refer to MSDS (available upon request).

#### 7.0 SHELF-LIFE

Up to six months in unopened container.

#### 8.0 AVAILABILITY

5 Gallon Pails

#### LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with Western Colloid instructions. Western Colloid does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at Western Colloid's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Western Colloid in writing at the addresses shown herein. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES OR LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE.

652\_0104a